

Mugnaini Series

MODEL: G180 x 140 PA

NEAPOLITAN DOME ENCLOSURE

COMMERCIAL GAS FIRED OVEN

CLEARANCES:

Install the oven with a minimum 1 inch clearance on sides and back to combustible construction. Consult the manual for enclosure instructions.

VENTING:

The oven can be vented in two methods:

- Direct vent using 8 inch chimney pipe listed to UL 103 HT and installed per UL 737.
- 2. Indirect vent using a Type 1 hood system installed per UL 2162.

SHELF:

Stainless steel shelf bolts to oven. Shelf to be covered with non-combustible material provided by installer.

WEIGHT: 4800 lb.

UTILITIES:

Provide 3/4" N.P.T. gas supply. 116,000 BTU natural or propane. 120VAC / 1.1 AMP electrical supply.

BURNER SYSTEM:

Spitfire New Generation Burner. Automatic w/ manual override.

NOTE:

The oven should be installed in accordance with all relevant local and national codes and in a manner acceptable to the authority having jurisdiction.

Progressive changes in technology and product development may necessitate changes to specifications without notice.







ANSI-Z83.1

11 ANSI/N 1.8

© COPYRIGHT 2013, Mugnaini Imports, Inc. May not be used without permission of copyright holder.



